

NB301 GEARBOX
(PARAMETER AND DIMENSION)
M2' 2000 N.M

NB301L M2'=2000N.m

	I	Mn ₂ (N.m)					P ₁	P _t (KW)	n ₁	n _{1max}	M _b	Brake	
		n _{2.h}	n _{2.h}	n _{2.h}	n _{2.h}	n _{2.h}							n _{2.h}
	1:	10000	25000	50000	100000	500000	1000000	(KW)	(n ₁ =1500)	(min ⁻¹)	(min ⁻¹)	(N.m)	制动器械
L1	3.4	2 000	2 000	1 750	1 700	1 350	1 100	30	7.5	1 750	3 500	440	4L
	4.4	2 000	2 000	1 750	1 700	1 350	1 100	30	7.5	1 750	3 500	440	4L
	5.8	1 700	1 450	1 300	1 300	1 300	1 050	28	7.5	1 750	3 500	400	4K
	7.2	1 150	1 150	1 150	1 150	1 150	940	18	7.5	1 750	3 500	260	4F
L2	11.5	2 000	2 000	1 750	1 700	1 350	1 100	15	7.5	1 750	3 500	260	4F
	15	2 000	2 000	1 750	1 700	1 350	1 100	12	7.5	1 750	3 500	260	4F
	19.8	2 000	2 000	1 750	1 700	1 350	1 100	10	7.5	1 750	3 500	160	4D
	25.6	2 000	2 000	1 750	1 700	1 350	1 100	8.2	7.5	1 750	3 500	160	4D
	32	2 000	2 000	1 750	1 700	1 350	1 100	7.5	7.5	1 750	3 500	100	4B
	41.5	1 700	1 450	1 300	1 300	1 300	1 050	5.2	7.5	1 750	3 500	100	4B
	51.8	1 150	1 150	1 150	1 150	1 150	940	3.6	7.5	1 750	3 500	50	4A
L3	38.8	2 000	2 000	1 750	1 700	1 350	1 100	6	7.5	1 750	3 500	100	4B
	50.9	2 000	2 000	1 750	1 700	1 350	1 100	4.9	7.5	1 750	3 500	50	4A
	66.1	2 000	2 000	1 750	1 700	1 350	1 100	3.8	7.5	1 750	3 500	50	4A
	87.8	2 000	2 000	1 750	1 700	1 350	1 100	3	7.5	1 750	3 500	50	4A
	108	2 000	2 000	1 750	1 700	1 350	1 100	2.5	7.5	1 750	3 500	50	4A
	114	2 000	2 000	1 750	1 700	1 350	1 100	2.4	7.5	1 750	3 500	50	4A
	142	2 000	2 000	1 750	1 700	1 350	1 100	2	7.5	1 750	3 500	50	4A
	185	2 000	2 000	1 750	1 700	1 350	1 100	1.6	7.5	1 750	3 500	50	4A
	230	2 000	2 000	1 750	1 700	1 350	1 100	1.3	7.5	1 750	3 500	50	4A
	299	1 700	1 450	1 300	1 300	1 300	1 050	1	7.5	1 750	3 500	50	4A
	373	1 150	1 150	1 150	1 150	1 150	940	0.55	7.5	1 750	3 500	50	4A
L4	297	2 000	2 000	1 750	1 700	1 350	1 100	1	6	1 750	3 500	50	4A
	386	2 000	2 000	1 750	1 700	1 350	1 100	0.8	6	1 750	3 500	50	4A

501	2 000	2 000	1 750	1 700	1 350	1 100	0.65	6	1 750	3 500	50	4A	
625	2 000	2 000	1 750	1 700	1 350	1 100	0.55	6	1 750	3 500	50	4A	
650	2 000	2 000	1 750	1 700	1 350	1 100	0.53	6	1 750	3 500	50	4A	
780	2 000	2 000	1 750	1 700	1 350	1 100	0.45	6	1 750	3 500	50	4A	
853	2 000	2 000	1 750	1 700	1 350	1 100	0.42	6	1 750	3 500	50	4A	
1024	2 000	2 000	1 750	1 700	1 350	1 100	0.35	6	1 750	3 500	50	4A	
1108	1 700	1 450	1 300	1 300	1 300	1 050	0.25	6	1 750	3 500	50	4A	
1329	2 000	2 000	1 750	1 700	1 350	1 100	0.27	6	1 750	3 500	50	4A	
1383	1 700	1 450	1 300	1 300	1 300	1 050	0.2	6	1 750	3 500	50	4A	
1659	2 000	2 000	1 750	1 700	1 350	1 100	0.22	6	1 750	3 500	50	4A	
1725	1 700	1 450	1 300	1 300	1 300	1 050	0.17	6	1 750	3 500	50	4A	
2153	1 700	1 450	1 300	1 300	1 300	1 050	0.14	6	1 750	3 500	50	4A	
2687	1 150	1 150	1 150	1 150	1 150	940	0.08	6	1 750	3 500	50	4A	
			M_{2max}=1.2×Mn₂(n₂×h=10 000)										

NB301R

M2'=2000N.m

I	Mn ₂ (N.m)						P ₁	P _t (KW) (ta=20°C)	n ₁	n _{1max}	M _b	Brake type
	n ₂ .h	n ₂ .h	n ₂ .h	n ₂ .h	n ₂ .h	n ₂ .h						
1:	10000	25000	50000	100000	500000	1000000	(KW)	(n ₁ =1500)	(min ⁻¹)	(min ⁻¹)	(N.m)	制动 器械
R2 6.9	1 200	1 200	1 200	1 200	1 100	930	15	12	1 750	3 500	260	4F
9.1	1 450	1 450	1 450	1 450	1 250	1 050	15	12	1 750	3 500	260	4F
11.8	1 700	1 450	1 300	1 300	1 300	1 050	14	12	1 750	3 500	260	4F
14.8	1 150	1 150	1 150	1 150	1 150	940	11	12	1 750	3 500	160	4D
R3 23.5	2 000	2 000	1 750	1 700	1 350	1 100	8	12	1 750	3 500	160	4D
30.8	2 000	2 000	1 750	1 700	1 350	1 100	7.7	12	1 750	3 500	100	4B
40.5	2 000	2 000	1 750	1 700	1 350	1 100	6.3	12	1 750	3 500	100	4B
52.6	2 000	2 000	1 750	1 700	1 350	1 100	5	12	1 750	3 500	100	4B

